



**QAQC LAB**

[www.qclabequipment.com](http://www.qclabequipment.com)

## Tight Head Drums (316L ss)

Volume 10L to 200L

**New**



Tight Head Drums are used throughout the world for handling and storing liquids and oils.

Tight Head Drums are made from hygienic 316L stainless steel. They have a standard 2" bung in the top as well as a second ¾" bung.

- Range of closed top Drums from 10L to 200L
- 316L stainless steel
- Silicone gaskets (FDA acceptable grade)
- Swaged sides for improved strength
- Made from 1.2mm stainless steel
- Not UN certified

Bottles & Containers

| Part No.    | Nominal Volume | Max. Diameter | Nominal Height | Bung Sizes | Material (Body & Bung) | Bung Gasket               |
|-------------|----------------|---------------|----------------|------------|------------------------|---------------------------|
| 675 A26610  | 10L            | 260mm         | 255mm          | 2" & ¾"    | 316L ss                | Silicone - FDA acceptable |
| 675 A26620  | 20L            | 289mm         | 401mm          | 2" & ¾"    | 316L ss                | Silicone - FDA acceptable |
| 675 A26650  | 50L            | 362mm         | 568mm          | 2" & ¾"    | 316L ss                | Silicone - FDA acceptable |
| 675 A266100 | 100L           | 458mm         | 700mm          | 2" & ¾"    | 316L ss                | Silicone - FDA acceptable |
| 675 A266200 | 200L           | 581mm         | 886mm          | 2" & ¾"    | 316L ss                | Silicone - FDA acceptable |

## Trolley

Our stainless steel Drums Trolleys are ideal for moving equipment around the factory. These sturdy trolleys have all wheel steering and two of the wheel are fitted with brakes.

- 304 stainless steel frame
- Includes 4 castors (2 lockable)
- Available from stock for fast delivery



| Part No.    | Max. Diameter Drum | Deck Height |
|-------------|--------------------|-------------|
| 675 A384320 | 320mm              | 135mm       |
| 675 A384420 | 420mm              | 135mm       |
| 675 A384500 | 500mm              | 135mm       |
| 675 A384600 | 600mm              | 135mm       |
| 675 A384740 | 740mm              | 160mm       |